


- ◆ GRIGLIATO STIRATO E SPIANATO
- ◆ WALKWAY MESH EXPANDED AND FLATTENED METAL
- ◆ METAL DEPLOYE ET APLATI POUR PASSERELLE
- ◆ STRECKMETALL FLACHGEWALZT MIT GITTERROST-MASCHE
- ◆ REJILLA ESTIRADA LAMINADA

SP 2



◆ **Materiale:** ACCIAIO FE DD 13
Interassi maglia: mm 112 x 40
Avanzamento: mm 9,5
Spessore: mm 4
Peso: KG/M² 16 + - 10%

◆ **Raw material:** MILD STEEL FE DD 13
Mesh pitch: mm 112 x 40
Strand width: mm 9,5
Thickness: mm 4
Weight: KG/M² 16 + - 10%

◆ **Matière:** ACIER DOUX FE DD 13
Entraxes: mm 112 x 40
Lanière: mm 9,5
Epaisseur: mm 4
Poids: KG/M² 16 + - 10%

◆ **Material:** STAHL FE DD 13
Achsabstände der Masche: mm 112 x 40
Stegbreite: mm 9,5
Dicke: mm 4
Gewicht: KG/M² 16 + - 10%

◆ **Material:** ACERO FE DD 12
Entreejes malla: mm 112 x 40
Ancho hilo: mm 9,5
Espesor chapa: mm 4
Peso: KG/M² 16 + - 10%

- ◆ RETI E GRIGLIATI STIRATI
- ◆ EXPANDED METAL
- ◆ METAL DEPLOYE
- ◆ STRECKMETALL
- ◆ METAL EXPANDIDO



RGS Schiavetti Srl
 Viale della Vittoria, 4
 15060 STAZZANO (AL)
 Tel. **39 0143 61295
 Fax **39 0143 633466
 www.rgs.it rgs@rgs.it