







|  <ul style="list-style-type: none"> ◆ LUNGA DIAGONALE ◆ LONG WAY MESH ◆ LONGUE DIAGONALE ◆ LANGE DIAGONALE ◆ DIAGONAL LARGA |  <ul style="list-style-type: none"> ◆ CORTA DIAGONALE ◆ SHORT WAY MESH ◆ COURTE DIAGONALE ◆ KURZE DIAGONALE ◆ DIAGONAL CORTA |  <ul style="list-style-type: none"> ◆ AVANZAMENTO ◆ STRAND WIDTH ◆ LANIERE ◆ STREGBREITE ◆ ANCHO HILO |  <ul style="list-style-type: none"> ◆ SPESSORE ◆ THICKNESS ◆ EPAISSEUR ◆ DICKE ◆ ESPESOR CHAPA |  <ul style="list-style-type: none"> ◆ ACCIAIO DC 04 ◆ MILD STEEL DC 04 ◆ ACIER DC 04 ◆ STAHL DC 04 ◆ ACERO DC 04 |  <ul style="list-style-type: none"> ◆ TRASPARENZA FRONTALE % ◆ OPEN AREA % ◆ TRANSPARENCE FRONTALE % ◆ OFFENE FLÄCHE % ◆ TRANSPARENCIA FRONTAL % |
|--|--|---|---|--|--|
| 225 | 35 | 15 | 1,5 | 10 +-10% | 26%~ |
| | | | 2 | 13,5 +-10% | |

- ◆ LAMIERA STIRATA PER SCHERMATURE
- ◆ EXPANDED METAL FOR COVERING
- ◆ METAL DEPLOYE POUR FACADES
- ◆ STRECKMETALL FÜR VERKLEIDUNGEN
- ◆ METAL EXPANDIDO PARA FACHADAS