

- ◆ MAGLIA PER ESSICCAZIONE LATERIZI
- ◆ MESH FOR DRYING BRICKS
- ◆ MAILLE POUR LE SECHAGE DES BRIQUES
- ◆ MASCHEN FÜR DIE TROCKNUNG VON BACKSTEINEN UND ZIEGELN
- ◆ MALLA PARA EL SECADO DE LADRILLOS

MR 110 X 40 - 8 X 3



This image is for illustrative purposes only, it may not accurately represent real mesh

◆ **Materiale:** ACCIAIO DD 13
Interassi maglia: mm 110 x 40
Avanzamento: mm 8
Spessore: mm 3
Peso: KG/M² 9 + - 10%

◆ **Raw material:** MILD STEEL DD 13
Mesh pitch: mm 110 x 40
Strand width: mm 8
Thickness: mm 3
Weight: KG/M² 9 + - 10%

◆ **Matière:** ACIER DD 13
Entraxes: mm 110 x 40
Lanière: mm 8
Epaisseur: mm 3
Poids: KG/M² 9 + - 10%

◆ **Material:** STAHL DD 13
Achsabstände der Masche: mm 110 x 40
Stregbreite: mm 8
Dicke: mm 3
Gewicht: KG/M² 9 + - 10%

◆ **Material:** ACERO DD 13
Entreejes malla: mm 110 x 40
Ancho hilo: mm 8
Espesor chapa: mm 3
Peso: KG/M² 9 + - 10%

- ◆ RETI E GRIGLIATI STIRATI
- ◆ EXPANDED METAL
- ◆ METAL DEPLOYE
- ◆ STRECKMETALL
- ◆ METAL EXPANDIDO



RGS Schiavetti Srl
 Viale della Vittoria, 4
 15060 STAZZANO (AL)
 Tel. **39 0143 61295
 Fax **39 0143 633466
 www.rgs.it rgs@rgs.it